

**forede**<sup>®</sup>

QUANZHOU FOREDE FIRE FIGHTING EQUIPMENT CO.,LTD.

[www.foredefire.en.alibaba.com](http://www.foredefire.en.alibaba.com)

### Flange Oblique Hydrant Valve

#### FRD-OF

Manufactured to BS5041 Part 1

#### Key Facts:

- **Body:** Copper Alloy to EN 1982
- **Hand Wheel:** Grey Cast Iron to BS EN 1561
- **Blank Cap:** Copper Alloy to EN 1982
- **Disc assembly:** Brass W/ replaceable facing rubber
- **Stem:** Brass
- **Chains:** SUS304
- **Cap:** ABS Plastic
- **Test Pressure:** Valve Seat@16.5Bar, Body@22.5Bar

*\*Optional Fitting* :Strap And Pad Lock For Securing Hand Wheel



Model	Pressure Rating	Outlet	Inlet Flange	Product NO.
FRD-OF65	PN16	2.5"BS336 Female Inst.	2.5" BS4504	H390YHN69R85P59

### Theard Oblique Hydrant Valve

#### FRD-OS

#### Key Facts:

Manufactured to BS5041 Part 1

- **Body:** Copper Alloy to EN 1982
- **Hand Wheel:** Grey Cast Iron to BS EN 1561
- **Blank Cap:** Copper Alloy to EN 1982
- **Disc assembly:** Brass W/ replaceable facing rubber
- **Stem:** Brass
- **Chains:** SUS304
- **Cap:** ABS Plastic
- **Test Pressure:** Valve Seat@16.5Bar, Body@22.5Bar

*\*Optional Fitting* :Strap And Pad Lock For Securing Hand Wheel



Model	Pressure Rating	Outlet	Inlet	Product NO.
FRD-OS65	PN16	2.5"BS336 Female Inst.	2.5" Male BSP	H210YHN69R85P32

### Flange Straight Hydrant Valve

#### FRD-SF

#### Key Facts:

Manufactured to BS5041 Part 1

- **Body:** Copper Alloy to EN 1982
- **Hand Wheel:** Grey Cast Iron to BS EN 1561
- **Blank Cap:** Copper Alloy to EN 1982
- **Disc assembly:** Brass W/ replaceable facing rubber
- **Stem:** Brass
- **Chains:** SUS304
- **Cap:** ABS Plastic
- **Test Pressure:** Valve Seat@16.5Bar, Body@22.5Bar

*\*Optional Fitting* :Strap And Pad Lock For Securing Hand Wheel



Model	Pressure Rating	Outlet	Inlet	Product NO.
FRD-SF65	PN16	2.5"BS336 Female Inst.	2.5" BS4504	H440YHN69R85P67

### Screw Straight Hydrant Valve

#### FRD-SS

##### Key Facts:

##### Manufactured to BS5041 Part 1

- **Body:** Copper Alloy to EN 1982
- **Hand Wheel:** Grey Cast Iron to BS EN 1561
- **Blank Cap:** Copper Alloy to EN 1982
- **Disc assembly:** Brass W/ replaceable facing rubber
- **Stem:** Brass
- **Chains:** SUS304
- **Cap:** ABS Plastic
- **Test Pressure:** Valve Seat@16.5Bar, Body@22.5Bar

*\*Optional Fitting* :Strap And Pad Lock For Securing Hand Wheel



Model	W.P.	Outlet	Inlet	Product NO.
FRD-SS65	PN16	2.5"BS336 Female Inst.	2.5" Male BSP	H310YHN69R85P47

### Flange Right Angle Hydrant Valve

#### FRD-RR

##### Key Facts:

##### Manufactured to BS5041 Part 1

- **Body:** Copper Alloy to EN 1982
- **Hand Wheel:** Grey Cast Iron to BS EN 1561
- **Blank Cap:** Copper Alloy to EN 1982
- **Disc assembly:** Brass W/ replaceable facing rubber
- **Stem:** Brass
- **Chains:** SUS304
- **Cap:** ABS Plastic
- **Test Pressure:** Valve Seat@16.5Bar, Body@22.5Bar

*\*Optional Fitting* :Strap And Pad Lock For Securing Hand Wheel



Model	W.P.	Outlet	Inlet	Product NO.
FRD-RR65	PN16	2.5"BS336 Female Inst.	2.5" BS4504	H450YHN69R85P68

### Thread Right Angle Hydrant Valve

#### FRD-RSA

##### Key Facts:

##### Manufactured to BS5041 Part 1

- **Body:** Copper Alloy to EN 1982
- **Hand Wheel:** Grey Cast Iron to BS EN 1561
- **Blank Cap:** Copper Alloy to EN 1982
- **Disc assembly:** Brass W/ replaceable facing rubber
- **Stem:** Brass
- **Chains:** SUS304
- **Cap:** ABS Plastic
- **Test Pressure:** Valve Seat@16.5Bar, Body@22.5Bar



Model	W.P.	Outlet	Inlet	Product NO.
FRD-RSA65	PN16	2.5"BS336 Female Inst.	2" BSP Male	H280YHN69R85P43

### Thread Right Angle Hydrant Valve

#### FRD-RSB

##### Key Facts:

##### Manufactured to BS5041 Part 1

- **Body:** Copper Alloy to EN 1982
- **Hand Wheel:** Grey Cast Iron to BS EN 1561
- **Blank Cap:** Copper Alloy to EN 1982
- **Disc assembly:** Brass W/ replaceable facing rubber
- **Stem:** Brass
- **Chains:** SUS304
- **Cap:** ABS Plastic
- **Test Pressure:** Valve Seat@16.5Bar, Body@22.5Bar



Model	W.P.	Outlet	Inlet	Product NO.
FRD-RSB6 5	PN16	2.5"BS336 Female Inst.	3" BSP Male	H240YHN69R85P37

### Bib Nose Flange Hydrant Valve

#### FRD-BF

##### Key Facts:

##### Manufactured to BS5041 Part 1

- **Body:** Copper Alloy to EN 1982
- **Hand Wheel:** Grey Cast Iron to BS EN 1561
- **Blank Cap:** Copper Alloy to EN 1982
- **Disc assembly:** Brass W/ replaceable facing rubber
- **Stem:** Brass
- **Chains:** SUS304
- **Cap:** ABS Plastic
- **Test Pressure:** Valve Seat@16.5Bar, Body@22.5Bar



Model	W.P.	Outlet	Inlet	Product NO.
FRD-RS65	PN16	2.5"BS336 Female Inst.	2.5" BSP	H585YHN69R85P94

### Flange Pressure Regulating Valve

#### FRD-PBF

##### Key Facts:

##### Manufactured to BS5041 Part 1

- **Body:** Copper Alloy
- **Blank Cap:** Copper Alloy
- **Chains:** SUS304
- **Stem:** Brass
- **Hand Wheel:** Grey Cast Iron
- **Blank Cap:** ABS Plastic
- **Disc Assembly :** Brass W/NBR
- **Test Pressure:** 30Bar



Model	Inlet Pressure	Outlet Pressure	Inlet	Outlet	Product NO.
FRD-FBF65	7-20bar	5-8bar adjustable	2.5" BS4504	2.5"BS336 Female Inst.	H750Y69R15P115
FRD-FBF80	7-20bar	5-8bar adjustable	3" BS4504	2.5"BS336 Female Inst.	H750Y69R15P

### Thread Pressure Regulating Valve

#### FRD-PBS

##### Key Facts:

##### Manufactured to BS5041 Part 1

- **Body:** Copper Alloy
- **Blank Cap:** Copper Alloy
- **Chains:** SUS304
- **Stem:** Brass
- **Hand Wheel:** Grey Cast Iron
- **Blank Cap:** ABS Plastic
- **Disc Assembly :** Brass W/NBR
- **Test Pressure:** 30Bar



Model	Inlet Pressure	Outlet Pressure	Inlet	Outlet	Product NO.
FRD-PBS65	5-20bar	5-9bar adjustable	2.5" Male BSP	2.5"BS336 Female Inst.	H560Y065R15P85
FRD-PBS80	5-20bar	5-9bar adjustable	3" Male BSP	3"BS336 Female Inst.	Customized

### Wedge Type Hydrant Valve

#### FRD-DF

##### Key Facts:

##### Manufactured to BS5041 Part 1

- **Body:** Gunmetal To BS1400 LG2
- **Chains:** SUS304
- **Stem:** Gunmetal
- **Hand Wheel:** Grey Cast Iron
- **Blank Cap:** ABS Plastic



Model	T.Pressure	Outlet	Inlet	Product NO.
FRD-DF65	24Bar	2.5"BS336 Female Inst.	2.5" BS4504 Flange	H680YHN69R85P103
FRD-DF65B	24Bar	2.5"BS336 Female Inst.	2" BS4504 Flange	H680YHN69R85P103
FRD-DFT65	24Bar	2.5"BS336 Female Inst.	2.5" Female BSP/BSPT	H520YHN69R85P79
FRD-DMT65	24Bar	2.5"BS336 Female Inst.	2.5" Male BSP/BSPT	H535YHN69R85P81